



OCÉ PSBLT

Universal Backlit Film Aqueous Inkjet Media
for use with dye and pigment ink on thermal and piezo inkjet printers.

Product Description

Océ PSBLT is a 9 mil matte surface, front print polyester backlit film that is water resistant* and compatible with pigment and dye inks. The matte surface reduces the impact of fingerprints for easy handling from printing to installation. The ink jet receptive coating produces super wide gamut for brilliant colors and sharp details. The water resistance and durability make it a great choice for longer-lasting indoor backlit displays and short-term outdoor displays. Océ PSBLT backlit film is optimized for pigment inks, but can be used with either pigment or dye inks.

SPECIFICATIONS

Physical properties*

- Caliper: 9 mil nominal
- Finish: matte one side
- Opacity: 68%
- Whiteness: 95%

*Target Values

Features

- Fast dry with pigment inks
- Water resistant
- Universal compatibility (Latex/aqueous/eco-solvent)
- Even light distribution
- Matte surface to reduce glare

Recommended Storage Conditions and Shelf Life

- Temperature 59°-86°F. (15°-30°C).
Relative Humidity 50%
- Repack opened rolls when not in use.
- Greater than one year at conditions noted above.
- Allow material to stabilize to room conditions 24 hours before use..

Environmental, Health & Safety

- No Material Safety Data Sheet required.
- Waste can be recycled (PET). Where recycling does not exist, disposal at a landfill or an approved incinerator is recommended.

Main Applications

- Backlit displays and signage
- Tradeshow displays
- Lightbox graphics and kiosks
- Window graphics

Printer/Ink Compatibility

Océ PSBLT is compatible with all thermal and piezo inkjet printers using water-based dye and pigment inks. Pigment inks are recommended to produce outstanding print quality when using either reflective or transmitted light. Dye based inks will provide a higher color gamut but inkfade can occur and drying times will be longer.

When using dye inks allow for longer drying times. For a complete compatibility chart on our website go to: www.csa.canon.com

Finishing Recommendations

Lamination may not be required for short term indoor graphics due to the water resistance of the coating. However, lamination will protect the image when not covered by glass and is always recommended. The setting for low-melt should be between 190-200 °F. Hand application of laminates is not recommended. The print should dry for 24 hours before laminating. When mounting to substrates such as PVC, Acrylic etc., a standard mounting adhesive is appropriate.

OCÉ PSBLT

Océ Display Graphics media for inkjet printers

Software Settings and Color matching

The ink jet receptive coating is engineered for better than 400% ink coverage. The white film setting in most RIP's is appropriate.

However, we recommend a custom ICC profile for optimal results. For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software.

Important

Printer and driver settings need careful set up to ensure the best performance. Appropriate ink loads must be set for the ink/printer combination being used.

*Water Resistance Guidelines

To obtain a high degree of water resistance, use only pigmented inks. Allow the print to dry for 24 hours before exposing to moisture. Lamination may not be required for short-term indoor applications. Ink saturation over 300% can affect the water resistant properties and show ink bleed. Dye based inks will yield good color gamut but bleeding may occur when the images get wet. Over laminating will not eliminate ink bleed unless the material is completely sealed to a non porous surface.

This information is presented as a general guide and is not a performance guarantee.

The user should independently determine prior to use the suitability of the material for the specific purpose.

SELECTED AVAILABLE ROLL SIZES

ITEM NUMBER	WIDTH X LENGTH	QTY. PER CARTON	CORE
PSBLT36100	36" x 100'	1 Roll	2"
PSBLT50100	50" x 100'	1 Roll	2"
PSBLT60100	60" x 100'	1 Roll	2"

Canon is a registered trademark of Canon Inc. in the United States and elsewhere. "Océ" is a trademark or registered trademark of Océ-Technologies B.V. in the United States and elsewhere. Océ ColorWave is a registered trademark of Océ-Technologies B.V. in the United States and elsewhere. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. © 2018 Canon Solutions America, Inc. All rights reserved.

IS-34251 CSA DS 6/15/18 CC/PDF

Canon

CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES

100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085

ocesuppliesoc@csa.canon.com

CSA.CANON.COM