



SPEC SHEET

ID8L

Luster Photopaper Aqueous Inkjet Media Product Description

An 8.5 mil (210 gsm) luster ("E" type) photo paper. Instant Dry ID8L is a premium resin-coated photobase meeting the demands for high quality photorealistic reproduction. The ultra white base with microporous coating means your prints will be instantly dry and water resistant; while the thinner base allows you to save money and still provide photographic output. Universal compatibility is optimized for today's wide gamut printers. Instant Dry ID8L optimizes natural skin tones and more neutral Lab values.

SPECIFICATIONS PHYSICAL PROPERTIES*

- Caliper: 8.5 mil
- Basis Weight: 210 gsm
- Gloss Level: (60°) 15%
- Opacity: 97%
- Color: L96, a = 2.00, b = -8.25
- Whiteness: 120 CIE

* Target Values

FEATURES

- True "E" Surface photographic look
- Instant Dry
- Photorealistic image quality
- Universal Compatibility
- High Ink Load limit
- Outstanding black and white quality

RECOMMENDED STORAGE CONDITIONS AND SHELF LIFE

- Temperature 59°-86°F. (15°-25°C).
Relative Humidity 30-70%
- Repack opened rolls when not in use.

- One year at conditions noted above.
- Allow material to stabilize to room conditions 24 hours before use.

ENVIRONMENTAL, HEALTH & SAFETY

- No Material Safety Data Sheet required.
- Waste not suited for recycling.

MAIN APPLICATIONS

- Photorealistic image reproduction
- Pre-press Proofing
- Indoor Posters

PRINTER/INK COMPATIBILITY

Recommended for use in most photographic, and display graphics inkjet printers including: Epson® Ultra Chrome and K3 series, Vivid Magenta series, Canon® PROGRAF® and IPF series, as well as Hewlett Packard® Z, series and HP5500 series printers. For a complete compatibility chart on our website go to: www.csa.canon.com

HANDLING RECOMMENDATIONS

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It is always recommended that cotton gloves be worn when handling inkjet coated materials. Rolls are supplied coated side out.

LAMINATING

Can be overlaminated with either hot or cold laminates Make sure that prints are completely dry prior to laminating.

IMPORTANT

Printer and driver settings need careful set up to ensure the best performance. Appropriate ink loads must be set for the ink/printer combination being used.

AQUEOUS INKJET MEDIA

Selected Available Roll Sizes

ITEM NUMBER	WIDTH X LENGTH	QTY. PER CARTON	CORE
ID8L24100	24" x 100"	1 Roll	2"
ID8L36100	36" x 100'	1 Roll	22"



CANON SOLUTIONS AMERICA

LFS IMAGING SUPPLIES
100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085
LFSimagingsupplies@csa.canon.com CSA.CANON.COM