



OCÉ VL6R OR VL6P

6.5 mil Matte White Vinyl with Removable or Permanent Adhesive Aqueous Inkjet Media for use with dye and pigment ink on thermal and piezo inkjet printers.

Product Description

A 6.5 mil (325gsm) water resistant calendared white PVC vinyl with permanent or removable adhesive. The VL6 is perfect for point of purchase applications. It produces bright, bold color images for decals, indoor window signage and many smooth surfaces using the removable adhesive. For permanent signage for short term outdoor graphics you can use the permanent adhesive for longer use. You can add protection to this product with pressure sensitive laminate as well for extra durability.

SPECIFICATIONS

Physical properties*

- Basis Weight -325 gsm
- Caliper: 6.5 mil
- Whiteness: > 130 CIE
- Opacity: 90%
- Gloss:@60° <2

*Target Values

Features

- Excellent Overall Print Quality
- Water resistant
- Removable or Permanent adhesive
- Indoor and outdoor use

Recommended Storage Conditions and Shelf Life

- Store in clean, dry area away from direct sunlight
- Temperature 60°-75°F. (15°-25°C). Relative Humidity 30-70%.
- Repack opened rolls when not in use
- Allow material to stabilize to room conditions 24 hours before use.
- One year at conditions noted above

Environmental, Health & Safety

- No Material Safety Data Sheet required.
- Waste not suited for recycling.

Main Applications

- Decals
- Short Term outdoor signage
- Indoor window signage
- Point of Purchase
- Floor graphics

Printer/Ink Compatibility

Océ VL6 is recommended for use in Océ ColorWave 700/900 printers. For the Océ ColorWave 700 printer, you can create a custom profile through Océ Web Tools. For the Océ ColorWave 900 printer, you can download an Onyx profile. Media comes on a 3 inch core. It's also compatible with traditional thermal and piezo inkjet printers.

Finishing Recommendations/Post Process

Océ VL6 performs well in finishing operations such as lamination (cold only) and kiss cutting or other graphic cutting printing systems

Important

Printer and driver setting need set up to ensure the best performance. Appropriate ink loads must be set for the ink/printer combination being used.

Color Profiles

ICC color profiles will improve image quality and optimize ink limits for improved drytime, wider color gamut, and more accurate color matching. The Océ ColorWave 700 Printer can create a custom media profile through Océ Web Tools. The Océ ColorWave 900 printer will get best results when using the Onyx profile which can be downloaded from the website.

OCÉ VL6 R OR P

Matte White Vinyl Aqueous Inkjet Media

This information is presented as a general guide and is not a performance guarantee. The user should independently determine prior to use the suitability of the material for the specific purpose.

SELECTED AVAILABLE ROLL SIZES

ITEM NUMBER	WIDTH X LENGTH	QTY. PER CARTON	CORE
VL6P24100	24" x 100'	1 Roll	3"
VL6P36100	36" x 100'	1 Roll	3"
VL6R24100	24" x 100'	1 Roll	3"
VL6R36100	36" x 100'	1 Roll	3"
VL6R42100	42" x 100'	1 Roll	3"
VL6R5060	50" x 60'	1 Roll	2"
VL6R6060	60" x 60'	1 Roll	2"

* R = Removable adhesive

P = Permanent adhesive

Canon is a registered trademark of Canon Inc. in the United States and elsewhere. "Océ" is a trademark or registered trademark of Océ-Technologies B.V. in the United States and elsewhere. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. © 2017 Canon Solutions America, Inc. All rights reserved.

IS-34189 CSA DS 3/17 CC/PDF

Canon

CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES
100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085
ocesuppliesoc@csa.canon.com
CSA.CANON.COM