



OCÉ 10DF

10 mil Blockout Display Film water resistant, Aqueous Inkjet Media for use with dye and pigment ink on thermal, piezo and latex inkjet printers.

Product Description

A 10 mil 100% synthetic blockout film coated for aqueous inkjet. Water resistant, blockout and no curl features make this a great choice for rollable displays, POP, indoor banners, transportation ads. Excellent image quality on multiple ink platforms—aqueous inkjet, latex, Océ ColorWave® 500/700/650 and 910 printers. The Océ 10DF is approved to for use in the Océ ColorWave 500/650/700 printers.

SPECIFICATIONS

Physical properties*

- Basis Weight - 235 gsm
- Caliper - 10 mil
- Opacity - 99%
- Brightness - >85 CIE

*Target Values

Features

- Printable PET Banner
- Excellent image quality
- Water resistant
- Cross platform compatible
- No curl
- Quick-dry semi matte finish

Recommended Storage Conditions and Shelf Life

- Store in original packaging and plastic bag. Best stored in cool dry area.
- Temperature 50°-86°F. (10°-30°C).
- Storage Humidity Range 20% non-condensing.
- Repack opened rolls when not in use

- One year at conditions noted above
- Allow material to stabilize to room conditions 24 hours before use.

Environmental, Health & Safety

- No Material Safety Data Sheet required.
- Waste is not suited for recycling.

Main Applications

- Roll-up Displays
- POP Graphics
- Indoor Banners
- Bus and subway advertising

Printer/Ink Compatibility

Océ 10DF is recommended for use in the aqueous pigment and dye and Latex printers. Remember to perform the media calibration function on the Océ ColorWave 500 and 700 printers. For the Océ ColorWave printers you will need to download the media profile from the www.csa.com/support section of the website.

Media Handling

To avoid smudges and marks on your finished print we recommend handling the coated surface while wearing cotton gloves. Store unused media in original packaging, vertically. For best results, let media acclimate to printing room conditions for 48 hours before use

Finishing Recommendations

Lamination is not required for Océ 10DF. However it does accept most pressure-sensitive and low-temperature hot laminating materials. Laminates with UV inhibitors help reduce fade and increase print durability.

Important

Printer and driver setting need set



OCÉ 10DF

10 mil Blockout Display Film water resistant, Aqueous Inkjet Media for use with dye and pigment ink on thermal, piezo and latex inkjet printers.

up to ensure the best performance. Appropriate ink loads must be set for the ink/printer combination being used

ICC Color Profiles

ICC color profiles will improve image quality and optimize ink limits for improved dry time, wider color gamut, and more accurate color matching. You can use at polypropylene printer driver for media choice if you do not have an outside supporting RIP, i.e. Onyx, Caldera, where you can make a custom ICC profile. The Océ ColorWave 650/500/700 Printers can use Océ 10DF profile.

This information is presented as a general guide and is not a performance guarantee. The user should independently determine prior to use the suitability of the material for the specific purpose.

Selected Available Roll Sizes

ITEM NUMBER	WIDTH X LENGTH	QUANTITY PER CARTON	CORE
10DFA36100	36" x 100'	1 Roll	3"



CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES
100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085
ocesuppliesoc@csa.canon.com
CSA.CANON.COM

Canon is a registered trademark of Canon Inc. in the United States and elsewhere. "Océ" is a trademark or registered trademark of Océ-Technologies B.V. in the United States and elsewhere. Océ ColorWave is a registered trademark of Océ-Technologies B.V. in the United States and elsewhere. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. © 2018 Canon Solutions America, Inc. All rights reserved.

IS-34211 CSA DS 6/15/18 CC/PDF