



OCÉ AQPOP

6 mil Universally compatible White Polyester Aqueous Inkjet Media for use with dye and pigmented inkjet printers.

Product Description

Océ AQPOP is a 6 mil (180 gsm), universally compatible white polyester roll up film with a back coating that blocks out light and provides 100% opacity. It is an economical product for trade show and point-of-purchase graphics that will be mounted on pop-up retractable display systems. Also compatible with latex printers and the Océ ColorWave® 500 and Océ ColorWave® 700 printers.

SPECIFICATIONS

Physical properties*

- Basis Weight - 180 gsm
- Caliper - 6 mil
- Whiteness - > 89 CIE
- Opacity - > 100%

*Target Values

Features

- Water resistant
- Universal compatibility
- 100% Opaque
- Scratch and abrasion resistant
- Lamination not required for short-term use

Recommended Storage Conditions and Shelf Life

- Ideal storage conditions are 70°F (21°C), 50% R.H. (controlled environment is highly recommended)
- Store in original packaging when not in use
- Optimal printing conditions are 60-80°F and 50% Relative Humidity
- Shelf life is one year at the conditions noted above

Environmental, Health & Safety

- No Material Safety Data Sheet required.
- Waste is suitable for recycling.

Main Applications

- Trade show and portable retractable displays
- Point-of-Purchase signage
- Posters

Printer/Ink Compatibility

Océ AQPOP is compatible with all thermal and piezo inkjet printers, using water-based dye and pigment-based inks. It is also compatible with UV, Latex and Océ ColorWave 650/500® and Océ ColorWave 700® printers.

Color Matching

For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software.

Software Settings

The inkjet coating on this product is engineered for better than 400% ink coverage. The white film setting in most RIP's is appropriate. However, we recommend a custom ICC profile for optimal results.

Handling Recommendations

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It is always recommended that cotton gloves be worn when handling inkjet coated materials. Rolls are supplied coated side facing out.

Laminating

It is always recommended that a protective laminate be applied after printing. Pressure sensitive laminates can be used. The print should be allowed to dry for 24 hours before laminating.



OCÉ AQPOP

6 mil Universally compatible White Polyester Aqueous Inkjet Media for use with dye and pigmented inkjet printers.

When mounting to substrates such as PVC, Acrylic, etc., a standard mounting adhesive is appropriate.

This information is presented as a general guide and is not a performance guarantee.

Water Resistant & Surface Protection

To obtain a high degree of waster resistance, use only pigmented inks. Allow the print to dry for 24 hours before exposing to moisture. Lamination is not required. Ink saturation over 300% can yield good color gamut, but bleeding may occur when the image gets wet. Over laminating dye-based inks will not eliminate image bleed, unless the material is completely sealed to a non-porous surface.

The user should independently determine prior to use the suitability of the material for the specific purpose.

Selected Available Roll Sizes

ITEM NUMBER	WIDTH X LENGTH	QUANTITY PER CARTON	3" CORE WITH 2" ADAPTER
AQPOP36100	36" x 100'	1 Roll	3"

Canon is a registered trademark of Canon Inc. in the United States and elsewhere. "Océ" is a trademark or registered trademark of Océ-Technologies B.V. in the United States and elsewhere. Océ ColorWave is a registered trademark of Océ-Technologies B.V. in the United States and elsewhere. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. © 2016 Canon Solutions America, Inc. All rights reserved.

IS-34224 CSA DS 10/16 CC/PDF



CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES
100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085
ocesuppliesoc@csa.canon.com
CSA.CANON.COM